

Installation guide

ELIMINATOR® Hermetic filter drier Type DML / DCL

023R9514

023R9514

Refrigerant temperature



T_{min} : -40 °C / -40 °F

T_{max} : 70 °C / 160 °F

Solder pure copper 	1.5, 03, 05, 08, 16, 30, 60 cu in.	$\frac{1}{4} - \frac{7}{8}$ in. ODM / ODF	PS/MWP 46 bar/667 psig
		$1\frac{1}{8}$ in. ODM / ODF	
	38, 41 cu in.	$\frac{3}{4} - \frac{7}{8}$ in. ODM / ODF	PS/MWP 35 bar/500 psig
		$1\frac{1}{8}$ in. ODM / ODF	
	75 cu in.	$\frac{3}{4} - 1\frac{1}{8}$ in. ODM / ODF	
Solder cu-plated 	03 – 60 cu in.	$\frac{1}{4} - \frac{7}{8}$ in. ODF	PS/MWP 46 bar/667 psig
		$1\frac{1}{8}$ in. ODF	
	75 cu in.	$\frac{7}{8} - 1\frac{1}{8}$ in. ODF	
Flare and face seal 	03 – 75 cu in.	$\frac{1}{4} - \frac{3}{4}$ in.	PS/MWP 46 bar/667 psig

